

## **DATASHEET**

## Product information CONN262010-CLAMP-10MTR

Name	CONN262010-CLAMP-10MTR
	2 Pin Molex Ditto current clamp connector with 10 meters Cable, shielded, PVC, 90°C max., with blunt cut end.
Product description	
Туре	CONN262010-CLAMP-10MTR
Description	2 Pin Molex Ditto current clamp connector with 10 meters Cable, shielded, PVC, 90°C max., with blunt cut end. Country of origin: EU HS: 90319000 - ECCN: No
Note	Shielding is not connected to the connector.  Standard available cable lengths (m): 05, 10, 15m.
Product specifications	
Connector type	2 Pin Molex Ditto, self-mating, non-gendered, tin over nickel contacts, heat shrink cable connection.  Mates with the iQunet Current Clamp connectors.
Connector material	PA66, UL 94V-0, white
Mounting type	Free hanging – in-line, friction lock
Cable length	10 meters, blunt cut end
Outer diameter	Ø5.5mm ±0.2mm
Inner strands	2 x 0.5mm², copper, twisted pair
Color code	Black (-) White (+) Shielding: bare conductor
Rated voltage cable	300 Vrms
IP rating cable assembly	None
Temperature range cable assembly	-20° to +105°C
Drawing & Picture	
	8.5 Blunt cut