


## DATASHEET

### Product information CONN262005-CLAMP-5MTR

<b>Name</b>	<b>CONN262005-CLAMP-5MTR</b>
	
	2 Pin Molex Ditto current clamp connector with 5 meters Cable, shielded, PVC, 90°C max., with blunt cut end.
<b>Product description</b>	
Type	CONN262005-CLAMP-5MTR
Description	2 Pin Molex Ditto current clamp connector with 5 meters Cable, shielded, PVC, 90°C max., with blunt cut end. Country of origin: EU HS: 90319000 - ECCN: No
Note	Shielding is not connected to the connector. Standard available cable lengths (m): <b>05</b> , 10, 15m.
<b>Product specifications</b>	
Connector type	2 Pin Molex Ditto, self-mating, non-gendered, tin over nickel contacts, heat shrink cable connection. Mates with the iQunet Current Clamp connectors.
Connector material	PA66, UL 94V-0, white
Mounting type	Free hanging – in-line, friction lock
Cable length	5 meters, blunt cut end
Outer diameter	Ø5.5mm ±0.2mm
Inner strands	2 x 0.5mm <sup>2</sup> , copper, twisted pair
Color code	<b>Black (-)</b> White (+) Shielding: bare conductor
Rated voltage cable	300 Vrms
IP rating cable assembly	None
Temperature range cable assembly	-20° to +105°C
<b>Drawing &amp; Picture</b>	
	